Data Sheet

STU-430 4.5-inch Signature Pad



W∂COM[°] for Business



Info@signatura.co.za www.signatura.co.za

STU-430 The versatile eSignature solution

Product Overview

Ideal for any electronic signing environment, the STU-430 is a versatile, full-featured, monochrome signature pad with a new thin design and a low-profile surface. The 4.5-inch LCD screen is large enough to capture longer handwritten electronic signatures, and accommodates soft buttons in addition to the signature area. The screen is easily readable in varying light conditions. State-ofthe-art encryption and a unique hardware ID ensure a secure signing experience.



Key Features & Benefits

- Practical electronic signature capture via the 4.5-inch monochrome, reflective LCD display that easily accommodates larger handwritten electronic signatures, as well as soft buttons
- Biometrically accurate electronic signatures using the digital pen with 1024 levels of pressure sensitivity
- Low maintenance effort and costs through the use of Wacom's patented electro-magnetic resonance (EMR) technology and batteryfree digital pen
- Outstanding durability via the scratch-resistant hardened cover glass, proven during testing to capture 500,000 electronic signatures with no surface wear

- particular signature

· Secure transactions enabled by stateof-the-art AES256 / RSA2048 encryption

 Secure PC connections via the integrated digital pen holder/USB cable lock combination, providing a dedicated area to place the pen when not in use, and a USB lock to prevent accidental disconnection of the USB cable

• Enhanced signature traceability through a UID (Unique hardware ID) for identifying the exact signature pad unit used for a

Enhanced device security with built-in Kensington® Security Slot

General Specifications

Ø	Dimensions (W x H x D)	6.3 x 6.9 x 0.4 inches / 161 x 174 x 11 mm		Pen storage	Per
	Weight (including stand)	0.6 lbs / 280 g		Connectivity security	US
(°°)	Main body color	Gray		Data security	Re wit
Ø	Power supply	Via USB, no additional power adapter required	0		
(7)	Power consumption	1.0 W maximum		Security lock slot	Yes
	Communication interface	USB	₽	Operating temperature, relative humidity	+4 (hu
				Storage temperature, relative humidity	-4

LCD Display

Display Type	F-STN	*	
Cover plate surface	Tempered glass		
Native resolution	320 x 200 pixels		

Pad and Pen

	Reading Technology	Electromagenetic Resonance (EMR)
\longleftrightarrow	Active area size	3.8 x 2.4 inches / 96 x 60 mm
	Coordinate resolution	2540 lpi / 0.01 mm/pt (non-interpolated)
+	Coordinate accuracy	±0.02 inches / ±0.5 mm (center)
	Report rate	200 points per second (non-interpolated)
	Pressure levels	1024 (non-interpolated)
Ĵ,	Encryption	AES256 / RSA2048

$\mathbf{\hat{O}}$ Package content

Signature software compatability

Miscellaneous

Wacom[®] for Business

Pen tray

USB cable locking system

Real time signature capture without internal pad memory

Yes, Kensington

+41° F to +104° F (+5° C to +40° C), humidity 30 % to 80 % RH, no condensing)

-4° F to +140° F (-20° C to +60° C), (humidity 30% to 90% RH, no condensing)

Compatible with Windows signature / eSign software and Wacom´s sign pro PDF and sign pro PDF Plug-in for Adobe Acrobat. For Windows, C++, .Net and Java development libraries available for developers (contact us for library and software availability in other development languages and platforms)

Signature pad, cordless and battery-free pen, USB cable (9.84 ft / 3 m), quick start guide, pen tether (nylon fiber, 19.7 inch / 50 cm)